- 1 IONIZING RADIATION
- 2 BIOLOGICAL EFFECTS
- RADIATION PROTECTION STANDARDS AND GUIDES
- 4 CONTROL OF RADIATION EXPOSURE
 - 5 INSTRUMENTATION
 - 6 BIOASSAY
- 7 PERSONNEL DECONTAMINATION
- 8 USE OF PROTECTIVE CLOTHING
- 9 INDUSTRIAL SAFETY
- PHYSICAL PROTECTION AND EMERGENCIES

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

\cap	IN	ΓR	$\cap \Gamma$	TT	\sim	TO	N
\ <i>)</i> .	1 I V			,,,		11.	1 4

TP-O.1 (NRC Logo)

- A. Instructor Self-Introduction
- B. Administration
 - 1. Complete course info sheets and pass in
 - 2. Ensure Evaluation Sheets are turned in after course
 - 3. Parking
 - 4. Food-lunch
 - 5. Restrooms
 - 6. Dress casual for 2nd day
 - 7. No Smoking in class
- C. Course Purpose
 - 1. Generic SAT
 - 2. Site Specific Training still required
 - 3. This course supports "good guy" letter from region

Normally 5 to 30 minutes TP-O.2

Avoid dresses

NRC resident

- · D. Course Schedule
 - 1. 7:40 a.m. start time
 - 2. 9:00 a.m. Break for Parking Meters

These are needed to ensure you get your

completion letter

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 3. First day ends 3:30 p.m. to meet shuttle
- 4. 2nd day depends on completion of exam

Make arrangements for transportation if you expect to take the full 1½ hours for exam

E. Exam

- 1. 50 questions multiple choice
- 2. 1½ hours to complete
- F. Review Manual content and organization

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

I.	IONIZING RADIATION:	TYPES,	QUANTITIES	AND
	LINITS			

A. Introduction

- 1. Section provides introduction to the types as well as the terms associated with the types ionizing radiation commonly found at nuclear plants
- 2. Chapter 1 Objectives

TP-1.1

B. The Atom

TP-1.2

- 1. Three basic sub-atomic particles
 - a. Neutron
 - Determines the isotope of a particular atom
 - Determines nuclear stability
 - Located in nucleus with protons
 - b. Proton
 - Determines the atom's atomic number
 - Located in the nucleus with neutrons

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- c. Electron
 - Determines the chemical stability of an atom
 - To be chemically stable, an atom will have a set number of electrons
- C. Ions TP-1.3
 - 1. Particles possessing an electrical charge, positive or negative
 - a. Free electrons
 - b. Beta particles
 - The same size as an electron, but emitted from the nucleus of an atom during radioactive decay
 - c. Alpha particles
 - Comprised of two protons, two neutrons
 - Positively charged
 - 2. Ionization
 - a. Occurs when an electron is removed from or added to a neutral atom
 - Results in a positively charged and a negatively charged particle, or <u>ion pair</u>

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

D. Radiation

1. Radiations result from unstable atoms which release energy and/or mass to become more stable or to reach a stable state

TP-1.4 Also originate from fission process

- a. Man-made
 - X-rays
 - Nuclear reactors
 - Atomic weapons
 - Medical radiation sources
- b. Naturally occurring
- 2. Radioactivity is defined as the spontaneous emission of radiation

TP-1.5

- a. Synonyms are activity and radioactivity
- 3. Radioactive material is defined as any material which emits radiation. It emits radiation over time due to radioactive decay.
- 4. Generally speaking, radiation is either ionizing or non-ionizing
- 5. Damage is done to cells by ionizing radiation by causing chemical ions to be generated in the cells creating an environment which is not conducive to living cells

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

6. Examples of non-ionizing radiation would be visible light from lighting fixtures, radiant heat, microwaves, etc.

E. Types of Ionizing Radiation

1. Five types of ionizing radiation

TP-1.6

- a. Alpha particle
- b. Beta particle
 - · Positively or negatively charged
- c. Gamma Ray
- d. X-ray
- e. neutron particle
- 2. Five common types of radiation interact with neutral atoms in either a direct or indirect manner to produce ions

Thus, referred to as ionizing radiation

3. These radiation types can also cause excitation of a neutral atom

This occurs without ionization

- a. Achieved by changing the energy level and stability of the neutral atom
- 4. Alpha Particles (α)
 - a. Identical to Helium nucleus

TP-1.7

• Two neutrons and two protons

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

≈ 0.0005 amu

Ъ.	Large particles emanated from the nucleus during radioactive decay	Size is ≈4 amu or 8000x mass of beta particle	
	• Particles have +2 charge	octa particie	
c.	Very energetic and have highest ionization potential	Energies in MeV range	
d.	Have lowest penetrating ability because so heavy	TP-1.8	
	• Travel in short straight line patterns	,	
e.	Can be shielded by a few sheets of paper or plastic, and will be stopped by the dead layer (epidermis) of the skin		
f.	An internal hazard to tissues		
g.	Source of alpha particles is primarily decay of heavy radionuclides	Transuranics are alpha emitters	
-	• U-235, Pu-239, Nd-144		
Beta	a Particles (β)	TP-1.9	
a.	Particles approximately the size of an	Very small mass	

5.

electron

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Emanated from the nucleus during radioactive decay
 - Can have either positive or negative charge depending on decay scheme
 - Beta minus (-) emission most predominant
- c. Energies in keV to MeV range

Lower ionization potential than α but higher than others

d. Can travel several feet in air but have low penetrating ability

TP-1.8

- Can penetrate material that an alpha cannot
- Can be shielded by low density material such as plastic
- e. Travel in "crooked" paths as they are easily deflected by atoms

Due to low mass and negative charge

- f. An internal hazard to tissues and external hazard to skin and lens of eye
- g. Source of beta particles is decay of activation and fission products
 - Fe-59, I-131, Cs-137, C-14, Sr-90, Co-58 (β⁺)

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

6. Gamma (γ) and X-Rays (x)

TP-1.10

- a. Electromagnetic energy
 - As the name implies (ray), they are pure energy
- b. No charge, no rest mass and low ionization potential
- c. Gamma rays (radiation) emanate from within the nucleus of atoms

Atoms with energies in the keV to MeV range

- Usually emitted concurrent with beta particle decay
- d. X-rays are emitted from the electron shells of an atom
 - The X-ray is generated when the electrons move from outer to inner orbit or
 - Bremsstrahlung-when high speed electrons are diverted by electromagnetic field

Can be generated by X-ray machines or natural X-ray capture

LESSON OUTLINE

NOTES/KEY AIDS Most penetrating of all five types and can TP-1.8 travel several hundred feet in air Travels in straight paths Due to no charge Can penetrate skin, dense tissue and Most effect whole body occupational ionizing radiation dose is received from - gamma radiation f. Gamma radiation is effectively shielded by: lead steel concrete (high moisture) water Source of gamma rays is the decay of activation and fission products Fe-59, Co-60, Kr-85, Xe-133, Cs-137

6. Neutrons (n)

TP-1.11

INSTRUCTOR

a. Neutral particle with mass \approx to that of proton

Mass ≈ 1 amu

- b. Emitted from the nucleus of an atom usually during some type of fission process
- c. Highly penetrating and can travel several hundred feet in air

Less penetrating, than γ & x-rays

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

d. Have wide range of energies

Less than one eV→MeV

- Travel path becomes more "crooked" as they slow down
- e. Have the lowest ionization potential of the five types
 - Ionization is indirect, normal interaction is collision with other atoms
- f. Whole body exposure problem, both an internal and external hazard

Neutron source inside the body very unlikely

g. Will decay into a proton and beta (-) particle pair after about 10 minutes

If still a free neutron

- h. Source of neutrons is primarily nuclear fission of reactor fuel (U-235, U-238)
 - Other sources include:

Spontaneous fission (Cf-252, Pu-239) and bombardment of beryllium with alpha particles

7. Summary of the characteristics of ionizing radiation

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- F. Quantities and Units
 - 1. Quantity is description of physical concept
 - 2. Unit is magnitude or measure of that quantity
 - 3. Radioactivity (Curie)

TP-1.12

- a. Quantity describing the number of decays/unit time (dps)
 - Independent of type of radiation
- b. Unit of radioactivity is Curie (Ci)

Note-Not required to memorize these numbers

• 1 Ci = $3.7 \times 10^{10} \text{ decays/sec (dps)}$

37 billion dps; mCi, μCi

• mCi = $3.7 \times 10^7 \text{ dps}$

more commonly

 $\mu \text{Ci} = 3.7 \times 10^4 \text{ dps}$

used

4. Specific Activity (Ci/g)

TP-1.13

a. "Concentration" of radioactive material

Activity/unit mass

- 1 milligram Co⁶⁰ ≈ 1 Ci
- "large pile" Uranium = 1 Ci
- b. Indicates how much material is needed to produce a certain decay rate

Higher Sp A, Greater hazard

INSTRUCTOR NOTES/KEY AIDS

LESSON OUTLINE

Hal	f-Life (T _{1/2})	TP-1.14
a.	Length of time required for ½ of the radioactive atoms to decay	
	• T ₁₆ is unique to each radionuclide	
b.	T_{\aleph} characterizes the rate of decay of a radionuclide	TP-1.15
c.	Examples	•
	• What fraction of the original quantity of a radionuclide will be left in 2 half-lives? Answer: 1/4	
	 What % of the original quantity of a radionuclide will decay away in 4 half- lives? 	
	Answer: 93.75%	
Exp	osure-Roentgen (R)	TP-1.16
a.	Amount of ionization (charge) produced per unit mass of air due to photon radiations	"What you could be exposed to" not dose you will
	 Radiation Field which is present (photons in air) 	receive
	a. b. c.	 radioactive atoms to decay T_N is unique to each radionuclide T_N characterizes the rate of decay of a radionuclide Examples What fraction of the original quantity of a radionuclide will be left in 2 half-lives? Answer: ¼ What % of the original quantity of a radionuclide will decay away in 4 half-lives? Answer: 93.75% Exposure-Roentgen (R) a. Amount of ionization (charge) produced per unit mass of air due to photon radiations Radiation Field which is present

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

b. Unit is Roentgen (R)

1 r = 0.000254 coul/kg air

Named after
Wilhelm
Roentgen who
discovered x-rays
Note: Revised
10 CFR 20 does
not use
Roentgen

7. Absorbed Dose (rad)

Radiation
Absorbed Dose

a. Measure of the energy deposited in living tissue

100 rad = 1 gray

- b. Does not take into account that different radiation types are <u>not</u> equally effective in causing biological damage or change
- 8. Dose Equivalent (rem)
 - a. Obtained by multiplying the absorbed dose (rads) X Quality Factor

 $rem = rad \times Q$

- Rem = Roentgen equivalent man
- b. Quality Factor (Q)-Weigh each type of radiation by its ability to produce biological damage in living tissue

TP-1.17

- Dependent on radiation's Linear-Energy-Transfer (LET)
- Radiation types which transfer higher amounts of energy over a short distance (high LET's) have higher Q's

TP-1.18

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

9. Dose Rates

TP-1.19

a. Rate at which exposure or dose is occurring

Measured in terms of time

 $dose rate = \frac{dose}{time}$

(STAY TIME) = <u>dose allowed ("limit")</u> dose rate ("dose receiving")

b. Example:

How long would a worker be allowed to stay in an area with a dose rate of 5 rem/hr if his allowed dose is 250 mrem?

Answer:

time (hr.) = $\frac{.250 \text{ rem}}{5 \text{ rem}}$ = 0.05 hr time (min.) = 0.05 hr x $\frac{60 \text{ min}}{1 \text{ hr}}$ time (min.) = 3 minutes

10. Summary of Quantities and Units

Refer class to Table 1-2B in Appendix for review

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

II. BIOLOGICAL EFFECTS

A.	Introduction					
	1.		ction provides overview of the biological effects ulting from exposure to ionizing radiation	•		
	2.	Ch	apter 2 Objectives	TP-2.1		
В.	B. Acute Vs. Chronic Exposure					
	1.		ute exposure to radiation is receiving a high se in a short period of time	TP-2.2		
	2.		ronic Exposure is low doses of radiation over a g period of time	TP-2.3		
		a.	Typifies occupational radiation exposure			
C.		Radiation has one basic biological effect and that is on cells				
	1. Acute radiation doses tend to kill cells					
		a.	Can kill so many cells that tissues or organs are damaged			
		b.	Causes rapid "whole body" response or Acute Radiation Syndrome	Expression of the cumulative lethal effect of radiation on many cells		

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 2. Chronic doses tend to damage (or change) cells
 - a. Don't necessarily cause immediate problem to any tissue or organ
 - b. The "cellular changes" may develop into cancer over the years
- 3. Internal vs. External Exposure

TP-2.4

- a. Internal exposure radiation exposure from radioactive sources inside the body
 - Enters body through
 - Inhalation
 - Ingestion
 - Absorption
 - Injection
- b. External exposure radiation exposure from radioactive sources outside the body
- D. Radiation Effects

TP-2.5

1. Result from interactions of radiation with the atoms of molecules of which cells are made

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

2. Direct Vs. Indirect Effects

- a. Direct effect is one in which radiation interacts with atoms which are critical to the survival of the cell
 - Example: the atoms needed to ensure the cells ability to reproduce
 - Chromosomal damage to DNA

3. Indirect Effects

- a. Most cells are made up of water and likelihood of radiation to interact with the life-sustaining atoms in a cell are small
- b. More likely for radiation to interact indirectly with water molecules and form free radicals which can recombine to form toxic compounds which can destroy cells
 - Example: hydrogen peroxide (H₂O₂)

E. Cell Sensitivity

Not all equally sensitive

- 1. Cells which replicate more quickly are more sensitive than ones more dormant
 - a. Replicating cells are dependent on correct order of DNA information in order to survive
 - Direct radiation interaction results in cell death
 - b. Dormant cells have little effects from direct interaction with radiation

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- **TP-2.6** 2. Cell sensitivity is based on rate of replication Lymphocytes and blood forming cells-most sensitive Reproductive and gastrointestinal cells-very b. sensitive Nerve and muscle cells-least sensitive Organ sensitivity correlates with cell sensitivity TP-2.7 3. Blood forming organs-most sensitive a. Reproductive and gastrointestinal tract-very b. sensitive
 - d. Muscle and brain-least sensitive
- 4. Must also consider relative importance of cells to overall body survival
 - a. Blood, GI and reproductive systems most important to body survival
- 5. Example: Malignant tumor/radiation therapy
- 6. Example: Embryo/Fetus

Skin-sensitive

c.

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

organs

F.	Hig	gh D	TP-2.8 "plume"	
	1.		gh doses of radiation have been received from rkplace accidents and other tragic events	Site examplés Rare at nuclear power plants
		a.	Radiation worker deaths from criticality accidents and irradiator accidents	power pames
	2.	Bio	ological effects of radiation exposure depend on	TP-2.9
		a.	Total dose	
		b.	Time interval over which dose is received	
		c.	Volume of tissue exposed	
		d.	Type of radiation	
	3.	Bio	ological effects increase as:	TP-2.10
		a.	Dose increases	
		b.	Volume of tissue exposed increases	
		c.	Time interval between doses decreases	Acute more damaging than chronic = less time to repair
		d.	LET of radiation increases	More energy transfer per unit distance in vital

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

4. LD 50/30

a. Dose at which 50% exposed will die within 30 days (or 60 days) without medical treatment

Sometimes called LD 50/60 TP-2.11 (curve)

b. LD $50/30 \approx 400 \text{ rad}$

In short time interval

- At 200 rad some will die, above 600 rad nearly all die
- Medical treatment can influence dose response curve, but only effective for doses <u>below</u> 1000 rad
- > 1000 rad fatal
- c. LD 50/30 provides statistical estimate

Does not indicate any one individual's probability

5. Biological factors influencing an individuals response to radiation exposure

TP-2.12

- a. Age
 - Immature organisms (younger) more sensitive than fully developed mature organisms

Embryo vs. middle aged adult

Very old organisms more sensitive than middle aged ones

Inability to repair damage as quickly

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Genetic Constitution
 - Differences in each individuals chromosomal traits (sensitivities)
- c. Sex
 - Females slightly less radiosensitive than males

Due to hormonal differences

- d. Health
 - Individuals in poor health are more radiosensitive

Impaired ability to repair

• Radiation can cause increase in sickness level

Effects on immune system

- e. Diet
 - Proper diet results in higher resistance to radiation
- 6. Acute Radiation Syndrome (ARS)

TP-2.13 Usually a whole body exposure (total body

irradiation)

a. Symptoms/signs

Below 200 rad these may be only symptoms which are indicative of

common flu

• Initial include: nausea, vomiting, fatigue and loss of appetite

• Three levels of effects (syndromes)

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

b. Hematopoietic (Blood System) Syndrome

TP-2.14

- Organ Exposed-Bone marrow
- Threshold-100 rad
- Duration of initial symptoms $\approx 2-3$ days
- Latency Period (feeling OK) ≈ 2-3 weeks
- Prognosis-Over 200 rad, death possible within 2-8 weeks
- Effects blood variations detectable by medical evaluation
- Cause of Death-infection, bleeding anemia
- Treatments-transfusions, antibiotics, isolation, bone marrow transplant
- c. Gastrointestinal (GI) Syndrome

TP-2.15

- Organ Exposed-Intestinal lining villi
- Threshold-≈ 500 rad
- Duration of initial symptoms ≈ 2-3 days
- Latency period ≈ 3-5 days
- Prognosis-over 1,000 rad death likely within 3-14 days

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- Effects-nausea, vomiting, diarrhea
- Cause of death-infection, bleeding, dehydration, electrolyte imbalance, circulatory collapse
- Medical treatment-none/make patient comfortable
- d. Central Nervous System (CNS) Syndrome
 - Organ Exposed-brain
 - Threshold ≈ 2,000 rad
 - Not much time for initial symptoms possible disorientation
 - Latency period-≈ 15 min.-3 hours
 - Prognosis-over 5,000 rad death likely within 3 days
 - Effects-Lethargy, convulsions, tremors, loss of muscle control, coma
 - Cause of death-respiratory/circulatory collapse
 - Medical treatment-none/make patient comfortable

In addition to blood system syndrome

TP-2.16 Often referred to as Cerebrovascular syndrome-brain's inability to control muscles

In addition to Blood and GI syndromes

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

7. Other high dose effects

TP-2.17

a. Skin

 Result usually from a low-energy X, γ or β radiation Energy is mostly deposited in skin surface

- Doses required are usually 300 rad and up
- Signs: reddening like sunburn, peeling, blistering, hair loss

b. Cataracts

- Threshold about 200 rad
- Neutrons effective in producing cataracts due to high quality factor and high water content of eye

Water effective in stopping neutrons

c. Sterility

- Requires significant doses to reproductive cells
- In males, (lower end of required dose range) sterility may be temporary
- 400 rad and above sterility may be permanent

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

G. Low Doses

1. Greatest concern is formation of non-lethal mutations in cells-(cancer)

Much more likely an effect of chronic doses

2. Three categories of chronic effects

TP-2.18

- a. Genetic
 - Effects suffered by future offspring of individual exposed

Exposed individual's reproductive system effected

- b. Somatic
 - Effect suffered by individual exposed

"Carcinogenic effect"

- c. In-utero
 - Effect suffered by developing, embryo/fetus (actually a special somatic effect)

Different from genetic effect

- 3. Genetic Effect
 - a. Mutation of reproductive (sperm, egg) cells which are passed to offspring

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Sources of genetic mutations:
 - · Physical-radiation
 - Chemical-many chemicals
 - · Biological-viruses
- c. NOTE: Radiation increases spontaneous mutation rates. Does Not Create New Mutations

TP-2.19 "Creature"

- d. Risk of mutations is directly proportional to dose with no threshold
 - Therefore, doses should be kept ALARA
- e. Genetic effects to this date have not been conclusive
 - Perhaps because the mutated egg/sperm would result in a spontaneously aborted non-viable organism

System would not "accept it"

- 4. Somatic Effects
 - a. Most significant risk is from occupational exposure (also is most well documented)

Cancer formation

• Reg Guide 8.29

TP-2.20

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Carcinogenic agents:
 - Physical-radiation
 - Chemical-cigarettes, many chemicals, etc.
 - Biological-viruses
- c. Examples of radiation induced cancer in populations

TP-2.21

- d. Risk
 - Risk of cancer determined from data at high doses and <u>estimates</u> at low doses

Reg Guide 8.29

• NRC adopts linear, non-threshold dose response curve (most conservative)

TP-2.22 Discuss linear relationship

- Indicates that there is no dose so low that it will not have some effect
- e. Incidence/Mortality

TP-2.23

 Risk estimates for radiation induced cancers is ≈ 2-10 excess cases per 10,000 exposed to 1 rem 1 in 4 chance of developing cancer regardless

- Risk of dying from cancer is ½ risk of getting cancer
- More exposure = more risk of cancer

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

5. In-Utero Effects

a. Radiation is also capable of producing physical malformations during fetal development

"Teratogenic" effects

TP-2.24

- b. Effects of in-utero exposure:
 - Intrauterine death
 - Growth retardation
 - Development abnormalities
 - Childhood cancers
- c. Probability and magnitude of effects are unfluenced by dose and stage of fetal development

TP-2.25

• Risk is highest during first trimester

Organs developing

- Risk of childhood cancer about same as adults, however, the risk of <u>all</u> in-utero effects is about 1-10/1,000 exposed
- Normal risks of fetal abnormalities are ≈ 5-30/1,000 live births

Medical procedures is largest source of in-utero exposure

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

d. Reg Guide 8.13

TP-2.26

• Recommends dose to embryo/fetus (pregnant worker) be kept less than or equal to 0.5 rem during entire gestation

Revised 10 CFR 20 makes this law for "declared pregnant women"

6. Reg Guide 8.29

TP-2.20 Chapter 2 Appendix

- a. Instruction Concerning Risks from Occupational Radiation Exposure
 - Provides instructions that should be provided to the worker concerning biological risks from occupational radiation exposure

TP-2.27

- b. Approximate risks of low dose radiation effects per 10,000 exposed/rad
 - Genetic-1 to 2
 - Somatic (cancer)-2 to 10
 - In-Utero (cancer)-2 to 10
 - In-Utero (all)-10 to 100
- c. Table 2-4 in 8.29 provides comparisons of radiation exposure risks with other activities

TP-2.28

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

III. RADIATION PROTECTION STANDARDS AND GUIDES

A. Introduction

- Section provides overview of regulations and guides for exposure to radiation and types of areas and signs commonly found at nuclear power plants
- 2. Chapter 3 Objectives

TP-3.1

3. NRC employees are exempt from 10 CFR 20must follow NRC Manual Chapter 0524 Chapter 3 Appendix

a. Basically same as part 20

B. ALARA Concept

- 1. Standards, regulations and guides provide limits and controls for protection against ionizing radiation
- 2. All personnel should strive to maintain their exposure ALARA, far below limits

Revised 20 "should" changes to "shall"

- C. Review of 10 CFR, Part 19 Notices, Instructions and Reports to Workers; Inspections
 - 1. Purpose

TP-3.2

a. Establishes the requirements for notices, instructions, and reports by licensees to workers participating in licensed activities and options available for workers to contact the NRC

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 2. Licensee's responsibilities
 - a. 19.11 Posting of Notices to Workers:

TP-3.3

- Licensee must provide:
 - Current copies of 10 CFR 19 and 20
 - Applicable operating procedures for licensed activities
 - Any notices of violation and licensee responses
- Notices must appear in sufficient numbers and within 2 working days of issuance
- b. 19.12 Instructions to Workers

TP-3.4

 Workers frequenting any portion of restricted areas must be kept informed of storage, transfer, protective measures, use, precautions, and radiation risks associated with the radioactive materials present Also covered in NRC Manual Chapter 0524

c. 19.13 Notifications and Reports to Workers

TP-3.5

- Licensee must provide workers with exposure records annually and upon termination of work
- Also, within 30 days of request, the licensee must provide former workers with exposure records for time of employment

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 3. 19.14 and 19.15 provided Regulations concerning inspections, presence of licensee representatives during inspections and consultation with workers by inspectors
 - a. IN 88-151 prohibits licensee from broadcasting arrival or progress of NRC inspectors
- D. Sources of Standards and Requirements
 - 1. NRC Manual Chapter 0524
 - a. Provides "standards" for radiation exposure of NRC employees
 - 2. 10 CFR Part 20
 - a. Regulation for control of occupational exposures and radioactive materials by NRC licensees
 - 3. Applicable Reg. Guides, other parts of Title 10 and Title 40 of CFR

TP-3.6

NRC employees visiting a site are expected to obey site regulatory and administrative limits

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- E. Radiation Dose Standards for Individuals in Restricted Areas
 - 1. Restricted area is an area in which access is restricted for purpose of controlling exposure to radiation

2. Dose Limits

- a. Whole Body (head and trunk, active blood forming organs, lens of eye, or gonads)
 - 1.25 rem/quarter
 - Increased to 3.0 rem/quarter with complete form 4
 - Must have documented accumulated occupational exposure <5 (N-18) rem to use 3.0 rem/qtr limit
 - N = age of individual

However, the only legal limit is 0524. If performance of your job requires longer stay time than allowed by a site admin limit, you should inform the site Radiation Supervisor that you will be exceeding the admin limits 10 CFR 20.101 NRC 0524. Part 2A

TP-3.7

Only penetrating radiation β , γ

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Extremities hands, forearms, feet and ankles
 - 18.75 rem/quarter
- c. Skin of the whole body
 - 7.5 rem/quarter
- d. Limits for individuals under 18 years of age are 10% (1/10)
- e. Internal Exposures
 - Limited by controlling amount of radioactive material inhaled, ingested or absorbed into body
 - Inhalation controlled by limiting product of:

Airborne Concentration X Exposure Time (Maximum Permissible Concentrations) (hours)

- Uptake limits 520 MPC hrs/quarter
 - MPC hr based on amount of internal radioactivity necessary to exceed maximum permissible dose standards for whole body
 - Estimated risk of one MPC hr is ≈
 2.5 mrem external exposure to whole body

Both penetrating and nonpenetrating radiations considered

10 CFR 20.103 NRC 0524, Part 2C

MPC-hrs

Based on continuous exposure for 40 hours per week for 13 weeks (1 quarter)

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- Administrative Limits
 - Used by licensees to control dose for periods less than a quarter and to support ALARA
 - Examples: 50 mrem/day 100 mrem/week
- Personnel Monitoring
 - Required for individuals likely to exceed 25% of limits

exceed 23%

1. Unrestricted Area

Posting Requirements

F.

- a. Area which is maintained with radiation levels under 2 mrem in 1 hour or 100 mrem in 7 consecutive days
- b. No posting requirements
- 2. General Posting Requirements for areas restricted for purpose of controlling radiation
 - a. Radiation symbol in magenta or purple on yellow background
 - b. Other appropriate information aiding in minimizing exposure may be provided on or near signs

Quarterly administration limits may be less than limits stated in NRG~~ 0524 and 10 CFR 20

10 CFR 20.105-20.204 NRC 0524 Parts 2C, 3B, 3C

500 mrem per year implied limit

		LESSON OUTLINE	INSTRUCTOR NOTES/KEY AIDS
3.	Restricted Area		TP-3.8
	a.	Must be posted if individual is likely to receive dose in excess of 2 mrem in any 1 hour or 100 mrem in seven consecutive days	
4.	Radiation Area		TP-3.9
	a.	Criteria	
		 Any area where the dose in 1 hour to a major portion of the whole body could result in 5 mrem or, in five consecutive days, in excess of 100 mrem 	
	b.	Radiation Symbol	
		CAUTION, (OR DANGER) RADIATION AREA	
	c.	Example	TP-3.10
5.	Hig	gh Radiation Area	TP-3.11
	a.	Criteria	
		 Any area where the dose to major portions of the body in 1 hour could be in excess of 100 mrem 	
	b.	Radiation Symbol	
		CAUTION, (or DANGER) HIGH RADIATION AREA	
	c.	Example	TP-3.12

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

6. Airborne Radioactivity Area

TP-3.13

- a. Criteria
 - Any area where radioactive materials exist in concentrations in excess of amounts listed in Appendix B, Table 1 or any area where airborne radioactive material exist in concentrations which, averaged over time/week individual is in area, exceed 25% amounts specified in Appendix B, Table 1
- b. Radiation Symbol

CAUTION, (or DANGER)
AIRBORNE RADIOACTIVITY AREA

c. Example

TP-3.14

7. Radioactive Material(s)

TP-3.15

- a. Criteria
 - Area or room in which there is used or stored an amount of licensed materials exceeding 10 times the quantity specified in Appendix C, or 100 times the quantities given for U or Th
- b. Posting
 - CAUTION, (or DANGER)
 RADIOACTIVE MATERIAL(S)
- c. Example

TP-3.16

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 8. Other Areas and Postings
 - a. Contamination Area (Zone)

TP-3.17

- Contains loose contamination
- Protective clothing required for entry
- b. Multiple postings

TP-3.18

- c. Part 50 of 10 CFR Appendix I (ALARA) limits annual doses in unrestricted areas from effluents or emissions to the following:
 - Limit per reactor from liquid effluents:
 - 3 mrem/yr total body or
 - 10 mrem/yr any organ
 - Limit per reactor from gaseous effluent submersion:
 - 10 mrad/yr from gamma or
 - 20 mrad/yr from beta
 - External dose from gaseous effluents:
 - 5 mrem/yr to the total body or
 - 15 mrem/yr to the skin
 - Limit per reactor from iodines and particulate released to the atmosphere:
 - 15 mrem/yr to any organ

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- d. Part 190 of 40 CFR (EPA) limits whole body dose in unrestricted area from fuel cycle operations:
 - 25 mrem/year
- e. Part 71 of 10 CFR (Transportation) has variety of limits based on shipping class and accessibility. General limits, not to exceed

TP-3.19

- 200 mrem/hr on contact 10 mrem/hr at 1 meter
- G. Recommendations Concerning Emergency Exposure
 - 1. NRC Manual Chapter 0524 Part 6

Not in 10 CFR 20

2. Maximum permissible dose values:

TP-3.20

- a. Saving Human Life 75 rem
- b. Recovery of Deceased Victims 12 rem
- c. Protection of Health and Property 25 rem
- H. Recommendations for Prenatal Radiation Exposure
 - 1. NCRP recommends maximum dose equivalent to fetus of 0.5 rem during entire gestation

TP-3.21

2. Reg Guide 8.13 provides guidance

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- I. The "Revised" 10 CFR Part 20
 - 1. "Old" Part 20 revised to incorporate recommendations specified in ICRP publications 26 and 30
 - a. After 12 years of deliberation, July 30, 1990 USNRC approved revised Part 20 as "final rule"
 - 2. USNRC and agreement state licensees must be in full compliance by January 1, 1994

Describe "agreement state"

3. Dose limit changes under Revised Part 20

TP-3.22

- a. Whole Body (total Effective Dose Equivalent) 5 rem/year
- b. Lens of eyes (Measured at a depth of .3 cm)- 15 rem/year
- c. Hands, forearms, feet and ankles (measured at a depth of .007 cm) 50 rem/year
- d. Skin of whole body (Measured at a depth of .007 cm) 50 rem/year
- e. Internal dose no separate limit, part of whole body dose
- f. Organ dose equivalent (External plus internal dose) 50 rem/year

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

4. Posting Requirement Changes Under the Revised Part 20

TP-3.23

- a. Radiation Area
 - Radiation symbol

CAUTION, (or DANGER) RADIATION AREA

Criteria

Area accessible to individuals in which radiation level could result in a dose equivalent in excess of 0.005 rem in 1 hour at 30 cm from the source or surface the radiation penetrates

Specifies distance from source and eliminates weekly limit

- b. High Radiation Area
 - Radiation symbol

CAUTION, (or DANGER) HIGH RADIATION AREA

Criteria

Area accessible to individuals in which radiation levels could result in a dose equivalent in excess of 0.1 rem in 1 hour at 30 cm from the source or surface the radiation penetrates

Specifies distance from source

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

c. Very High Radiation Area

TP-3.23 (cont'd)

Radiation symbol

GRAVE DANGER, VERY HIGH RADIATION AREA

Criteria

Areas accessible to individuals in which radiation levels could result in absorbed dose in excess of 500 rads in 1 hour at 1m from the source or surface the radiation penetrates

Not defined in "old" Part 20

- d. Airborne Radioactivity Area
 - Radiation symbol

CAUTION, (or DANGER)
AIRBORNE
RADIOACTIVITY
AREA

Criteria

A room, enclosure, or area in which airborne radioactive materials, composed wholly or partly of licensed material exist in concentrations..

In excess of DACs specified in Appendix B

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

To degree that without respiratory protection individual could exceed in 1 week, an intake of 0.06% of the ALI or 12 DAC-hours

e. Radioactive Material(s)

TP-3.23 (cont'd)

• Radiation symbol

CAUTION, (or DANGER)
RADIOACTIVE
MATERIAL(S)

Criteria

Area or room in which there is used or stored an amount of licensed material exceeding 10 times the quantity of such material specified in Appendix C

Appendix C values were revised

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

IV. CONTROL OF RADIATION EXPOSURE

A. Introduction

1. Purpose

Section provides basic guidelines for participants in this course to maintain their radiation exposure as low as is reasonably achievable while at a nuclear power station.

- 2. Chapter 4 Objectives
- B. Sources of Radiation

TP-4.1

Instructor should point out that due to differences in design between a PWR and a BWR, source location will differ

- 1. General Reactor Designs
 - a. Overall goal is controlled criticality
 - b. General arrangement
 - Fuel assemblies-made of a large number of fuel rods
 - Fuel rods-made up of fuel pellets in a sealed tube

Definition
Criticality:
When the
number of
neutrons
released by
fission is equal
to the number of
neutrons
absorbed plus
the number of
neutrons
escaping

LESSON OUTLINE

INSTRUCTOR **NOTES/KEY AIDS**

Control rods-moveable assemblies of neutron absorbing material. Can be moved out of the core to increase the active volume of the core. Rapid insertion "scrams" the reactor for a quick shutdown.

Commonly cadmium, hafnium, or boron

Basic Components

TP-4.2

Active core

TP-4.3

- 1) Location of the fuel where the fission process takes place
- Moderator

Only used in thermal reactors

- Material to thermalize fast neutrons
- Reflector
 - Material to decrease the loss of neutrons from the core by scattering many back
 - 2) Thermal reactors
 - a). Typically use the same material as the moderator

Common moderators are ordinary water, heavy water (deuterium oxide), carbon (graphite), and beryllium

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 3) Other reactors
 - a) Some material to reflect without moderating the neutrons
- Heat removal system
 - 1) Coolant
 - a) Medium circulated through the core to remove the heat from fission
 - 2) Heat sink
 - a) PWR's use a steam generator to remove the heat from the coolant
 - b) Research and other reactors (such as BWR's) may use some sort of cooling towers or ponds to cool in conjunction with "condensers"
- Control systems
 - 1) Control rods
 - a) The most common method of starting and stopping the chain reaction

Coolants used have been liquid water, liquid sodium, organic compounds, gases, air, carbon dioxide, and helium

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 2) Poisons
 - a) Burnable poisons placed in the fuel rods
 - b) Injectable poisons to shutdown the reactor
- 2. Major Reactor Types
 - a. Production reactors
 - Used for the production of ²³⁹Pu
 - b. Research reactors
 - Used for materials studies on effects of the reactor core environment
 - Used for potential future designs
 - Large number of potential and existing designs, however, most common is "swimming pool" reactor-a water moderated and reflected reactor in a large pool of water

Found at many universities

- c. Power reactors
 - Nuclear reactors designed to produce electricity
 - Light water reactors include:

Boiling water reactors (BWR), and

TP-4.4

LESSON OUTLINE INSTRUCTOR NOTES/KEY AIDS Pressurized water reactors (PWR) TP-4.5

- Heavy water reactors are of Canadian design
- Fast breeder reactors are an experimental model in U.S.

TP-4.6

Fission:

3. Fission Process

- a. Generates very high levels of gamma and neutron radiation
- b. Biological shields and other components inside containment limit radiation levels in routine work areas
 - Reactor shutdown ceases the fission process, and resulting "prompt" radiations
 - Main source of neutrons

4. Fission Products and Decay

a. Radioactive decay of fission products is a major source of radiation exposure inside containment during shutdowns and reactor refueling.

Nuclear fission occurs when a heavy nucleus absorbs a neutron and splits into two new nuclei with the release of large amounts of energy and neutrons

Refueling: The process of removing spent fuel, or the process of replacing/shuffling fuel elements in the core TP-4.7

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Activation product decay is considered the main source of radiation exposure to plant personnel
- Activation products can be found anywhere reactor coolant circulates, leaks, or is processed
- d. Fission products are found in the reactor coolant. If defective fuel elements exist, they may have to be considered as contributors to personnel exposures

Activation products:
TP-4.8
Products (or objects) which have become activated by neutron absorption and are therefore radioactive

- 5. Steam/Turbine/Condensate Systems
 - a. Radiation sources within the reactor coolant may be found in steam and condensate systems

 PWR-leak from primary coolant system to secondary system may be present

BWR-The coolant becomes the steam.
 Much higher radiation levels are found in steam turbine systems

TP-4.9

PWR-Pressurized Water Reactor BWR-Boiling Water Reactor

¹⁶N, high energy gamma,-major source of BWR turbine floor personnel exposure

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 6. Waste Treatment Systems
 - a. Liquid Radwaste Treatment
 - Involves the removal and concentration of activation and fission products through filtration, evaporation, ionexchange, settling and decay
 - Components involved include:
 - Catch and holding tanks
 - Ion exchangers
 - Evaporators
 - Pipe Systems (chases)
 - b. Solid Radwaste Treatment
 - Source: Liquid waste that has been processed
 - Involves packaging, compacting, and handling of waste in the solid form
 - Other sources: Small radioactive components, rags and associated debris
 - Solid waste sources include:
 - Resins
 - Filters

These components should be isolated or shielded due to potential high personnel exposures

TP-4.10

Classified as low level waste

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

7. Spent Fuel Storage

TP-4.7 TP-4.8

a. Pools

- Used for storage of spent fuel and other tools and reactor components
- Many feet of water used for reducing the exposure level in the general vicinity of the pool
- Sources of spent fuel storage personnel exposures include:
 - Fuel assemblies
 - Activated components
 - Stored materials
 - Fragments
 - Crud
- Factors that may contribute to personnel exposures around spent fuel storage areas include:
 - Radiation streaming
 - Flotation
 - Snagging
 - Equipment movement

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Dry Storage
 - Heavily shielded containers are being approved for the storage of older fuel.
 These containers are made up of concrete and steel.

TP-4.11

• Radiation levels around these containers are expected to be relatively low.

TP-4.12

- 8. Examples of Other Sources
 - 1. Other sources of radiation include:
 - · Penetrations through walls and shields
 - Incore instruments
 - · Small reactor components
 - Transfer tubes/spent fuel movement
 - Calibration operations (including radioactive sources)
 - Reactor coolant and waste processing samples
 - Plant Operations

Radiation levels vary with plant operating stations

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- B. Control of External Radiation Exposure
 - 1. Time

TP-4.13

a. Minimize the length of time exposed to radiation source

Discuss methods

- Pre-job planning
- · Pre-job briefings
- b. Calculate and remember the "stay time" prior to entering the radiation or high radiation areas

Discuss the concept of "stay time"
TP-4.14

2. Distance

TP-4.15

a. Maximize the distance from the radiation source

Discuss methods

- Pre-job review of area
- Knowledge of radiation source locations
- Pre-job discussion with HP's
- Don't wander into areas of unknown dose rates or conditions
- b. Radiation exposure varies inversely as the square of the distance from a small source

Inverse square law

• Example: Double the distance, exposure rate decreases by a factor of 4

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- c. Radiation exposure decreases by a factor of 2 if the source is large when compared to the distance
 - Example: If distance is doubled, the rate will decrease by a factor of 2

3. Shielding

TP 4-.16

a. Keep as much shielding between you and the radiation source as possible

Examples:

- Use existing shielding
- Pre-job briefings
- Pre-job planning
- b. Use available components as shielding when possible

TP-4.17

- c. Avoid being in the "line of sight" of radioactive sources
- d. Gamma radiation is the main contributor to radiation dose received by personnel at nuclear power plants

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

C. Contamination Control

1. Contamination: Radioactive material in an unwanted location

TP-4.18

- a. Controlled to:
 - Limit external exposure
 - Prevent internal exposure
 - Reduce the size of the areas requiring special controls
 - · Reduce radioactive waste processing
- b. Benefits of minimizing contamination:
 - Further reduce exposures
 - Minimize internal depositions
 - Ease of access into areas
 - Ease of egress out of areas
 - Minimize protective clothing requirements
- c. The prevention or limiting of intake is important to keeping total dose ALARA

Instructor should ask for other benefits

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

D. Control of Internal Radiation Exposure

- 1. Introduction
 - a. The majority of contamination in power plants results from leaking activation products

Reactor coolant system during maintenance evolutions

- 2. Contamination forms
 - a. Solid fine particles
 - Hot particles or "fleas" (special case) very small particles with high activity
 - Can settle on surfaces or remain airborne

If a hot particle is on the skin, the limit is 75 μ Ci-hours; if it is not on the skin, the skin limit applies

- b. Liquid
 - Exists due to leaks and/or spills
 - May become dry (solid)
- c. Gaseous

Example I¹³¹

• Result from gases produced in reactor

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

TP-4.19

TP-4.20

TP-4.21

3. Categories and Detection

- a. Personnel contamination: any form of radioactive contamination on personnel (including skin contamination)
 - Normally detected by a sensitive GM detector such as frisker, personnel monitor, or portal monitor

b. Categories

- Fixed
- Loose-can be inhaled, ingested, or deposited on skin
- Airborne-can be inhaled, ingested

c. Detection

- Direct surveys detect fixed
- Smears (swipes) detect loose contamination and are counted using a sensitive GM detector
- Air sampling detects airborne contamination and is usually counted in a laboratory

Licensees have site-specific limits

Normally 100 cm² in the shape of an "S"

TP-4.22

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

d. Action Levels

- Depend on type, location and area use
- Depend on licensee procedures
- Types include:

Personnel-any detectable 50-100 cpm above background

Removable (Beta/Gamma)-1000 dpm/100 cm²

Removable (Alpha)-20 dpm/100 cm²

TP-4.23 100 cpm = 1000 dpm when instrument efficiency is 10 percent

4. Contamination control

- a. Primary purpose: Reduces the risk of personnel contamination
- b. Examples of controls:
 - Engineering controls such as controlled/filtered ventilation zones, HEPA filters, catch trays
 - Housekeeping throughout the facility
 - Conduct routine maintenance to stop leaks
 - Post and control contaminated areas

TP-4.24

TP-4.25
Special attention
paid to RCA's
where
maintenance
work is
performed

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- Minimize the number of people entering contaminated areas
- Requiring/conducting a whole body survey upon exiting a contaminated area
- c. Controls implemented by individuals include:
 - Entering contaminated areas only when necessary/authorized
 - Proper use of PC's
 - Proper use of respirators
 - Avoid high contamination levels as practicable
 - Avoid use of synthetic clothing
 - Avoid floor drains, areas under open stairways
 - Avoid control boundaries and points
 - Complete a whole body survey upon exiting a contaminated area
- 5. Airborne Contamination Control (MPC-Hrs)
 - a. Control of personnel exposure to airborne radioactivity is accomplished by:
 - Limiting the exposure time and airborne concentrations (MPC's)

Due to affinity for staticallycharged particles

TP-4.26 TP-4.27

MPC-Hrs

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

b. Accomplished by:

- Utilizing engineering controls such as filtered ventilation systems
- Calculating estimated MPC-Hrs prior to entry
- Taking all reasonable action to minimize exposure
- Use of respirators

TP-4.28 Must be respirator qualified

E. Exposure Monitoring

- 1. Thermo Luminescent Dosimeters (TLD's)
 - a. Normally required to be worn when entering a radiation area or controlled area
 - b. Monitors whole body exposure
 - c. Normally worn on upper front torso between neck and waist
 - Multiple/special TLD's may be requiredmonitor other body locations, extremity and skin exposure
 - d. Periodic and special (as needed) processing provides exposure data
 - e. Film badges may be used instead of TLD's

Review 10 CFR 20, NRC 0524 criteria for assigning personnel monitoring devices

Define extremities

Periodic means every month. Special means high dose rate jobs, lost dosimetry

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

2. Pocket dosimeters

- a. Used for real-time monitoring
- b. Check frequently (minimum every 30 minutes)
- c. Used to update exposure record and control exposure until TLD is processed
- d. Should not be abused
- e. If dropped should be read. If off-scale notify HP
- f. Should not be taken apart
- 3. Digital/Alarming Dosimeters
 - a. Used for monitoring and controlling exposures
 - b. Used inside high radiation areas
 - c. Also known as "chirpers"
- 4. Other monitoring
 - a. Frisking
 - b. Other techniques
 - c. Identify/quantify exposure
 - d. Air sample results
 - e. Exposure time determination

equipment, etc.
Also known as
Self Reading
Dosimeters
(SRD's) or
Pocket Ion
Chambers
(PIC's)

i.e., dropped, submerged in liquids, etc.

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

F. Radiation Work Permit

TP-4.29

- 1. Normally required for entry into controlled areas
- 2. Standby RWP's may be used
- 3. Special RWP's are required depending on the job(s) to be performed
- 4. Serve the following functions:
 - a. Specifies general work information
 - b. Maps out the radiological hazards
 - c. Specifies personnel instructions
 - d. Specifies dosimetry requirements
 - e. Specifies dress out requirements
 - f. Specifies respiratory protection requirements
 - g. Specifies monitoring requirements
 - h. Specifies equipment (if any) which is needed to complete work
 - i. Establishes radiological/contamination limits associated with a specific job
 - j. Specifies other requirements
 - k. Provides special instructions (as required)

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

	5.	Adherence to the RWP:			
		a. Controls contamination	Controls contamination		
		• Protective apparel		alkala, va	
		Monitoring requirement	ents		
		b. Minimizes exposures			
		Administrative dose li		_Imposed by licensee	
		• Protective apparel	ncensee		
		Respiratory protection	n equipment		
		• Personnel monitoring	requirements		
		c. Increases job efficiency	Review the RWP with attendees		
G.	Exposure Control Cards (Dose Cards)		•		
	1.	Used for daily accounting of ex	and posure TP-4.31		
	2.	Used in conjunction with RWP	"s		
	3.	Used for evaluating ALARA co	ompliance Newer system may use computer software	ems	
	4.	Each individual is responsible for completeness	for accuracy and Instructor Review Dos Cards using		

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

H. Surveys

TP-4.32

- 1. Individuals must be able to view and understand
- 2. Ask HP or escort for clarification (if needed)
- 3. May be attached to an RWP
- 4. Note areas of high radiation/contamination levels
- 5. Not areas of low radiation/contamination levels
- 6. Identify "hot spots" and "low-dose" waiting areas
- 7. Purpose of performing surveys
 - a. Establishing stay times
 - b. Identify need for radiation shielding
 - c. Identify radiation, high radiation, and very high radiation areas
- 8. All reported results must be accurate or else problems such as overexposure or unplanned exposure may result

Note:
"ALARA Areas"
"Low Dose
Areas"
Some licensees
post these areas

A survey is a study to (1) find the radiation or contamination level of specific objects or locations within an area of interest; (2) locate regions of higher than average intensity; i.e., hot spots

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 9. Specific types of surveys/Radiation surveys can be done on either a routine basis or to determine specific conditions
 - a. Routine surveys
 - · Radiation Area surveys
 - High Radiation Area surveys
 - Hot Spot surveys
 - General Area surveys
 - b. Surveys to determine specific conditions
 - Job coverage (work area) surveys
 - c. Radiation Area surveys
 - Establishes point at which a radiation area begins
 - Establishes extent of radiation area
 - d. High Radiation and Very High Radiation Area surveys
 - · Establishes boundary
 - Establishes extent

Generally occupied work areas

Review definition of High and Very High Radiation Areas

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- e. Hot Spot surveys
 - Locates points on components where radiation levels exceed general area radiation levels by a specified amount

Usually about four times the general area radiation level

- f. General Area surveys
 - Performed to monitor levels of background radiation throughout a site
- g. Work Area surveys
 - A radiation survey in work areas throughout the site to verify protection factors that are important to personnel working in those areas
 - Specific job coverage situations
- I. As Low As Reasonably Achievable (ALARA)
 - 1. Acronym for As Low As Reasonably Achievable
 - 2. Any amount of radiation exposure may cause effects
 - 3. Maintaining exposures ALARA will minimize the potential for long term effects
 - 4. What is reasonable?

Background radiation is the steady level of radiation in the environment

For on-going or frequently used work areas

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

5. Goals

- a. Each individual as well as licensee should set goals of maximum exposure for planned work
- b. Setting of aggressive goals and striving to meet or exceed will result in lower overall exposures
- c. Lower exposures reduce risk
- 6. ALARA Responsibility
 - a. It is the responsibility of each employee to maintain his/her own dose as low as reasonable achievable
- 7. ALARA Procedures
 - a. Good Practices/Common Sense
 - · Keep your mind on the business at hand
 - Distractions are hazardous in themselves, even more so in a radiological hazard area
 - Communicate with HP personnel

Each licensee sets its own goals

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Follow directions
 - Follow radiological instructions
 - Adhere to radiological and safety postings
 - Don't just look at radiological signs, understand the implications before you enter an area
- c. Familiarize yourself with work area layout(s) prior to starting job
- d. Obtain all of the tools you will need prior to starting job
- e. Review radiological condition of area(s)
- f. Identify general location of radiation source(s) when entering work area(s)
- g. Do not linger in radiation areas. Retreat to low dose area(s) when the job is completed
- 8. Reg. Guide 8.8, "Information Relevant to Ensuring that Occupational Radiation Exposures at Nuclear Power Stations will be As Low As Reasonably Achievable"
 - a. Provides information relevant to attaining goals and objectives for planning, designing, constructing, operating, and decommissioning a light water reactor nuclear power station to meet the criterion that personnel exposures be ALARA.

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Goals/objectives presented should be used for all nuclear power stations
- c. Revision 3, 1978
- d. Provides programmatic guidance for ensuring exposures are ALARA

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

V. INSTRUMENTATION

A. Introduction

1. Purpose

Provide a brief overview of instruments used to detect and measure radiation levels

2. Chapter 5 Objectives

TP-5.1

B. Measuring and Detecting Radiation

- 1. Detecting radiation is the act of determining in real time whether radiation is present or not
- 2. Measurement is the act of determining how much is or was present (if any)

C. Dosimetry

- 1. Subtopic of instrumentation.
- 2. Special devices are used to measure the amount of radiation to which an individual has been exposed and this information is used to ensure compliance with federally imposed dose limits and to maintain an historical record of the individual's accumulated radiation dose

TP-5.2

3. External Dosimetry

TP-5.3

a. External dosimetry is action of determining the amount of radiation dose received by an individual from sources located outside the body

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Useful for monitoring doses from penetrating radiation such as x-rays, gamma rays and neutrons
- c. Also possible to monitor the dose to the skin surface from non-penetrating radiation such as beta
- d. Alpha is of no concern to external dosimetry
 - alpha particles do not have sufficient energy to reach vital tissue if incident on the surface of the body

4. Internal Dosimetry

- a. Internal dosimetry is action of determining the amount of radiation dose received by an individual from radiation sources that have been taken into the body
- TP-5.4

- b. The radiation emitted by the material exposes vital internal organs
- c. Relative hazards are directly opposite to those from external sources in terms of the Linear Energy Transfer of the radiation of interest
- d. Alpha particles deposit all of their energy in vital tissues and are thus the most hazardous
- e. Penetrating x-rays and gamma rays can easily escape and thus deposit only a small fraction of their energy in vital organs

α Cannot escape from body

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- f. Betas are both an external and internal hazard since
 - They have enough energy to penetrate the sensitive skin tissues from the outside
 - Expose vital tissues from the inside
- g. Neutrons are not considered an internal hazard
 - Few radioactive materials spontaneously emit neutrons
- h. Internal dosimetry will be further discussed in the section on Bioassay

This section will deal exclusively with external dosimetry sometimes called personnel dosimetry

Note: During the following instrument descriptions, the instructor demonstrates actual use of sample instruments.

- D. Personnel Dosimeters
 - 1. Three types

TP-5.5

- a. Pocket dosimeters
- b. Film dosimeters
- c. Thermoluminescent dosimeters (TLD's)

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

E. Pocket Dosimeters

TP-5.6

- 1. Used for the dual purpose of detecting the dose as it is being received in real time and measuring how much was received
- 2. Direct Reading Dosimeters usually of the pencil type design.

TP-5.7

- a. Individual reads dosimeter by peering through it like a mini telescope.
- b. Dose is indicated by the "hairline" on the scale.

3. Principles of Operation

- a. Hairline is initially set at zero by placing dosimeter in a charging device which distributes similar charges on the moving and fixed wire loops
- b. Similar charges cause mobile wire loop to be repelled and when fully charged, loop appears to be super imposed over the zero position on the scale
- c. As dosimeter is exposed to radiation, the ions produced dissipate the charge causing the repulsion between the loops to decrease
 - As the repulsion decreases, the mobile loop moves across the scale

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

TP-5.8

- 4. Indirect Reading
 - a. Must be read with a charger/reader
 - b. Workers are unable to monitor their dose as it is being received.
 - c. Can be useful in situations where a result is required sooner then can be provided by either film dosimetry or TLD
- 5. Digital Alarming Dosimeters (DAD)
 - Indicate the accumulated dose using a digital
 - b. Worker presses a button to see their current dose.
 - c. Major advantage

display.

- Emit an audible signal (beep) when a certain amount of radiation is detected.
- Some can preset alarm to trigger at some accumulated dose value
 - e., 100 mrem
- Some models have a second alarm which can be set at a predetermined dose rate
 - e., 1000 mrem/hr

Some direct reading dosimeters have LED displays which are normally blank. Worker can perform task knowing that when alarm sounds they can leave before exceeding limits

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

5. Pocket Dosimetry Characteristics

a. Range - Pockets have a specified range over which they are effective

- TP-5.9
- Important to know approximate maximum dose you are likely to receive to be able to select a dosimeter with the appropriate range
- As an example, a 0 to 20 rem pencil dosimeter won't help you to measure a 100 millirem dose
- Pocket dosimeter should read zero before being used

Not critical if there is a small dose already on it, as long as it's noted at the time of issue

b. Fragility

- Subject to false readings
- If you drop them they can move up or down scale
- Should always be read in the proper orientation (right side up and not upside down or standing on end)

Use a filament to indicate dosethey are fragile

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

c. Leakage

- · Can be affected by charge leakage
- A leaking charge will always result in an upscale movement which will result in a false positive reading
- If there is a question about the proper operation of the dosimeter, retreat to a low-dose area and contact the radiological controls technician

d. Environment

Can be suspectable to environmental conditions such as humidity

F. Film Badges

- 1. Device used for measuring beta, gamma, and neutron radiation by means of a piece of radiation sensitive film similar to x-ray film or photographic film
- 2. Radiation striking the film causes atomic and molecular changes which when chemically developed cause the film to be darkened
 - a. Black areas means exposed
 - b. Clear areas means not exposed

Since based on electrical principles

TP-5.10

The density of the dark areas indicate how much radiation was received

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 3. Typically constructed of plastic to allow gamma radiation to penetrate to the film inside
 - a. Also use a small opening, called a window, to allow a section of the film to be exposed to both beta and gamma radiation
- 4. Major advantage
 - a. Produces a permanent image of the radiation exposure which can be kept almost indefinitely
- 5. Film is sensitive to environmental conditions
 - a. Heat will cause film to fog
 - May overestimate the dose
 - b. Film will fade if not developed soon after use.
 - · May underestimate the dose
- 6. Film also has a range problem
 - a. As dose goes higher the film gets darker but at some point it gets as dark as it will ever get
 - b. After this point it will not respond to additional dose and will underestimate the amount of dose received

The range at which this occurs is generally at a very high total dose

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- G. Thermoluminescent Dosimeters (TLD's)
 - 1. TLD's have virtually replaced film as method of measuring beta and gamma radiation dose

TP-5.11

- 2. TLD's are crystals which have the ability to store information indicating how much radiation they were exposed to
 - a. Information is in form of electrons which move to higher energy levels when exposed to radiation
 - b. Electrons remain trapped in these levels until the crystal is heated
 - Heat causes the electrons to fall back to their initial levels and when they do, stored energy in the form of light is emitted
 - Amount of light emitted is proportional to the amount of energy initially absorbed by the crystal
 - c. Substances commonly used as TLD material
 - Lithium fluoride (LiF)
 - Calcium fluoride (CaF₂).

Can be of almost any form or shape

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- d. Badges have more than one chip and various overlying filters to assist in identifying the energy and type of radiation which caused the exposure
 - Commercially available TLD's are designed to simulate the skin, lens of the eye and whole body

Discuss measurement depths and density thicknesses

- e. TLD's do not provide a permanent record
 - When a TLD is heated the results are transferred to either a printout or computer database

H. General Dosimetry Rules

TP-5.12

- 1. Don't forget to wear one when it is required
- 2. Don't forget to turn it in for evaluation when you exit the radiation area, and
- 3. If you should lose your dosimeter while in a radiation area, or if your pocket dosimeter reads off scale, *LEAVE THE AREA*.
 - a. As you leave, notify anyone in the area, particularly if your pocket dosimeter is off scale
 - They may wish to check to see if their dosimeter is off scale

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

I. Instruments

1. Survey Meters

- a. Typically portable radiation detection instruments designed to be used in the field, under less than ideal conditions
- b. Typically have an accuracy of \pm 10-20%
- c. Principle use is to help evaluate the current situation and make an intelligent decision based on the results
- d. Basic Operating Principle
 - Radiation being detected or measured interacts with the atoms of a substance (gas, liquid or solid) and ionizes the material (creates free electrons and positive ions)
 - In some cases the ions are collected directly (gas filled and solid state detectors)
 - In others the light emitted by the atoms as they return to normal is measured (TLD's) or the light emitted is used to generate photoelectrons which are collected (scintillation)

TP-5.13

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

e. Check Operability

- Calibration Check to see if the instrument is past due on its calibration.
- Range Will the instrument cover the radiation or contamination levels expected?
- Physical condition Does the instrument have obvious damage?
- Allow the instrument to adjust to differences in environmental conditions, such as significant difference in temperature, by turning it on and giving it time for the readings to settle out
- Perform a battery check by selecting the battery test option

 Response to radiation - Expose the instrument to a source of radiation of sufficient strength to get a response TP-5.14

If past due do not use instrument

Keep the instrument in this mode for about a minute to ensure that the batteries are not close to expiring

If it does not respond or responds incorrectly, do not use the instrument

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

f. Check Applicability

TP-5.15

- Types of radiation Will the instrument detect the type of radiation (alpha, beta, gamma, neutron and/or x-ray) that is of interest?
- Energy detected Most instruments have a low energy cut-off so that they will not detect radiation below a specified energy. If that energy cut-off is above the energy of the radiation of interest then the instrument will not respond properly

A neutron flux meter set up for fast neutrons will not adequately detect or measure thermal neutrons

- Energy response ideally an instrument should have a flat response. If an instrument does not have a flat energy response then the under or over response must be compensated for, perhaps by applying a correction factor
- Response time indicates how fast the display tells the actual radiation level

Technically, the response time is that amount of time required to indicate 90% of the actual level

- For most instruments the response is very quick. Some instruments have a variable response
- "Do I know how to use it?" this is the most important question. Ensure that you know how to use the instrument prior to entering a radiation field

A fast response gives less accuracy than a slow response

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- g. Features Beta discrimination
 - Many Instruments have a movable beta shield

TP-5.16 TP-5.17

- This is simply a thick cover for the detector which, when used, prevents the betas from being detected
- With the beta shield closed the instrument is only detecting penetrating gamma radiation
- With the beta shield open, the instrument detects both beta and gamma radiations
- By subtracting the two values and applying a correction factor the presence and relative magnitude of beta radiation can be determined
- h. Battery Life is typically over 100 hours but is affected by the type of batteries and temperature

Radiofrequency - from a RF transmitter can cause false positive and erratic readings

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- j. Electrical fields in the form of static electricity can cause false positive readings
- k. Sensitivity to a particulate radiation such as alpha and beta is sometimes given as a percent

May be referred to as "efficiency"

 Sensitivity indicates what percentage of the particles actually emitted will be detected by the instrument

2. GM Instruments

TP-5.18

- a. Typically used to detect beta and gamma radiation
- b. Used to check objects and personnel for contamination by frisking
- c. Instrument scales are usually in counts per minute (cpm)
- d. Some instruments have scales in mR/hr. Since GM instruments do not have a flat energy response these instruments are only accurate at the energy at which they were calibrated

TP-5.19

e. The principle advantage of a GM detector is sensitivity and rapid response

INSTRUCTOR LESSON OUTLINE **NOTES/KEY AIDS** TP-5.20 f. Frisker is a portable GM survey meter such as an Eberline E-520 or RM-14 The probe is connected to the meter by a cable and is commonly used for personnel contamination monitoring Handheld is the other common type of GM survey meter likely to be encountered TP-5.21 A typical model is the Xetex 305B where detector is part of the instrument and is small enough to fit in the average shirt pocket TP-5.22 Ionization chamber Ionization chambers are typically air filled Ionization chambers operate at a lower voltage then GM detectors Produces less ion-electron pairs Ionization chambers collect all ion pairs created by the radiation and are

3.

therefore very accurate

Ionization chambers have a flat energy response and yield accurate readings over a wide range of gamma and beta energies

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- d. The Eberline RO-2 and RO-2A are typical of ionization chambers that are commercially available
 - The difference between the two models is that the ranges of the RO-2A are a factor of 10 greater than the RO-2
- 4. Teletector is essentially a high range instrument for revaluating radiation levels without unnecessarily exposing the individual
 - Has a detector at the end of a pole that can be extended up to 15 feet in some models
- 5. Displays come in two varieties, analog and digital
 - a. Both communicate the same information and respond at the same speed
 - b. Human perception causes the analog display to appear faster and more accurate even
 though both are reacting identically to fluctuations in radiation levels

TP-5.23

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

VI. BIOASSAY

- A. Introduction
 - 1. Purpose

Provide a brief overview of the principles of bioassay including whole body counting and biological sampling to evaluate internal contamination.

B. Chapter 6 Objectives

TP-6.1

- 1. Measurement of radioactive material in the body
- 2. Also called internal dosimetry
- C. Bioassay Techniques/Categories
 - 1. Bioassay may be accomplished by:
 - a. Whole body counting
 - Also known as in-vivo measurements

TP-6.2

• Method of determining the amount of radioactive material physically present in the body by detecting the penetrating radiation emitted from inside the body

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Biological sampling
 - Also known as in-vitro measurement

TP-6.3

- Method of determining how much radioactive material is present in a sample collected from the body (e.g., urine) and then calculating how much material is actually in the body based on how much was in the sample
- 2. Basic categories of bioassay

TP-6.4

- a. Baseline
 - Performed to determine if an individual has previously had material deposited internally
- b. Routine
 - Performed at regular intervals to determine if any radioactive material is being taken into the body during routine work activities
- c. Diagnostic

S .. ~~

 Done when there is a known or suspected internal exposure

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- D. External/Internal Exposure
 - 1. Basic methods of protection from external sources

TP-6.5

- a. Time
- b. Distance
- c. Shielding
- 2. Basic methods of protection from internal sources

- a. Once inside there is no method of completely eliminating the material quickly
- b. The best protection is to not let the radioactive material get inside. This can be accomplished by:
 - Using engineering controls
 - Obeying postings
 - Wearing protective clothing
 - Using respirators
 - Containing the materials
 - Not working in a contaminated area with open wounds

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

3.	Inta	kes	TP-6.7	
	a.	Radioactive material can get inside the body by several pathways:		
		• Inhalation		
		• Ingestion		
		• Absorption		
		• Puncture		
	b.	Of the four pathways, inhalation is the most common	••	
4.	Distribution			
	a.	Material within the body moves around based on solubility or transportability		
	b.	Soluble	TP-6.8	
	-	 Means that a substance is easily distributed in water or bodily fluids such as blood and urine 		
	c.	Transportable	TP-6.9	
		 Means that a substance is easily transferred (without being dissolved) from one organ system to another 	(e.g., from the lungs to the GI system)	

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

Uptake 5.

- Dependent on chemical, not radiological properties of the substance
- The fraction of the intake that enters the b. blood stream or is deposited in a critical organ

TP-6.10

Revise 10 CFR

Critical Organ 6.

20 That body site whose damage by radiation TP-6.11

will result in the greatest harm to the individual

- b. Each radionuclide may have a different critical organ
 - Cs-137 Muscle

TP-6.12

- Sr- 90 Bone
- I-131 Thyroid

E. Whole Body Counting

Direct measurement of internal radioactivity using organ counters or whole body counters

- Individual may be evaluated: 2.
 - TP-6.14 Standing a.
 - TP-6.15 b. Sitting
 - Lying down c.

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 3. The amount of shielding will be a major contributor to the smallest amount of radioactive material detectable.
- 4. The system may be:
 - a. Open
 - b. Partially shielded
 - c. Fully shielded
- 5. Counting Time
 - a. May vary from 1 minute to 30 minutes or longer
 - b. The longer the count, the smaller the amount of material detectable

For low level systems pre-World War II battleship steel is used because it was manufactured prior to nuclear weapons testing and Co-60 tracers in blast furnaces

Sometimes called the minimum detectable activity (MDA)

- 6. Detectors
 - a. The detectors typically used for whole body counters are
 - Sodium iodide (high efficiency but low resolution), germanium (low efficiency but high resolution)

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Efficiency
 - The ability to detect all of the radiation being emitted
- c. Resolution
 - The ability to distinguish between gamma rays having different energies
- 7. Organ counter
 - a. Basically the same as a whole body counter except that the detectors are focused on specific organs where the radioactive material is likely to be located
- 8. Specificity
 - a. Whole body counters can not distinguish the origin of the radiation
 - b. External skin contamination will result in an over estimation of the amount of radioactive material within the body
- 9. Advantages/Disadvantages

- a. Advantages of whole body counting
 - Provides a rapid assessment of internal contamination
 - · Can localize the site of deposition

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- Does not depend on the solubility or excretion rate
- The range of error is usually low
- b. Disadvantages of whole body counting
 - Sensitive to external contamination
 - Primarily limited to gamma emitters above 100 KeV
 - Requires elaborate, complex and expensive equipment
 - Gives no information on time that the intake occurred
- F. Biological Sampling
 - 1. Biological Elimination
 - a. Radioactive material may exit the body via several pathways in conjunction with these substances:

- Urine
- Breath
- Sputum
- Blood

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- Nasal Mucous
- Feces
- Sweat
- b. The rate at which radioactive material is removed by the body is very important and must be predictable
- 2. Half-life
 - a. Radiological Half-Life

TP-6.18

- The length of time required for half of the radioactive atoms to decay
- b. Biological Half-Life

TP-6.19

- The length of time required for the body to eliminate one half of the material
- c. Effective Half-Life

- The combined effect of both radiological and biological half-lives
- $T \frac{1}{2} \text{ eff} = \frac{T\frac{1}{2}_R \times T\frac{1}{2}_B}{T\frac{1}{2}_R + T\frac{1}{2}_B}$

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

3.	Excretion Rate		
	a.	Based on several factors	
		The material	
		Route of entry into the body	
		Time after intake	
		Organ in which the material is deposited	
		Biological factors of individual exposed	
	b.	The first four factors are predictable but the final factor is unpredictable	
	c.	Since the individuals unique metabolism is unknown we use a "reference" or "standard" man or woman to predict the excretion rate	
4.	Screening		TP-6.22
	a.	Nasal smears are one example of a screening method	
	b.	Not used to measure the amount of intake but can estimate the magnitude	
5.	Urinalysis		TP-6.23
	a.	Urine is a common body product collected for evaluation of the intake/uptake of radioactive materials	
	b.	Feces in some circumstance could be a better	

indicator of initial intake

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

c. Advantages of urinalysis

TP-6.24

- Most radionuclides are eliminated to some extent
- Alpha, beta and gamma emitters can be readily identified
- Many samples can be processed simultaneously
- Collecting urine samples has a minimum impact on worker time
- Biological sampling involves low cost

d. Disadvantages of urinalysis

- There is a time lag between sample collection and analysis
- There must be enough radionuclide in the sample to be detected
- Analytical procedures are time consuming
- Excretion rates vary with individuals and with time
- Insoluble particles will not be excreted in the urine
- The individual may not follow instructions for voiding the sample

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

G. Dose Assessment

TP-6.26

- 1. The hazard of internally deposited radionuclides depends on:
 - a. Amount of material
 - b. Effective half-life
 - c. Critical Organ
 - d. Energy and type of radiation
- 2. Acute/Chronic Exposure
 - a. Acute exposure

TP-6.27

- Any intake of radioactive material resulting from a single event
- b. Chronic exposure

TP-6.28

 Any intake (usually at a low rate) which occurs continuously or periodically over a long period of time

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

3. Maximum Limits

....

Revised with 1991 version of 10 CFR 20

a. Maximum permissible body burden (MPBB)

TP-6.29

- The amount of a radionuclide which, if inside the body, will give the maximum dose allowed by regulations to the whole body
- Currently 5 rem whole body dose
- b. Maximum permissible organ burden (MPOB)

TP-6.30

- The amount of a radionuclide which, if inside the body, will give the maximum dose allowed by regulation to the critical organ
- Currently 15 rem/year to any single organ excluding bone, skin, gonads, and thyroid

Limit to skin and thyroid is 30 rem/year, limit to gonads and uniformly deposited nuclides in the body is 5 rem/year

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- c. Maximum permissible concentration (MPC)
 - The MPC is based upon an MPOB that will result in a limiting dose rate after 50 years of exposure
 - That concentration of radioactive material in air which if taken into the body at the rate of 520 MPC-hrs per quarter will result in either a MPBB or MPOB

TP-6.31 See Appendix B for values. Also similar values for water

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

VII. PERSONNEL DECONTAMINATION

A. Introduction

- 1. This section provides an understanding of the importance of personnel decontamination and the techniques used to remove contamination from personnel.
- 2. Chapter 7 Objectives

TP-7.1

B. Goals of Personnel Decontamination

TP-7.2

- 1. Reduce Exposure
- 2. Minimize intake of contaminants
- 3. Prevent contamination spread
- C. Identification of Contamination
 - 1. Personnel surveys
 - a. Whole body surveys required when exiting known or potentially contaminated areas
 - b. Spot or localized surveys when exiting areas with a low potential for contamination

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 2. Monitoring Devices
 - a. Hand held frisker probes
 - b. Automated personnel monitors
 - c. Hand and foot monitors
 - d. Portal monitors

TP-7.3 TP-7.4 Show any available examples of frisking devices. Frisking units are typically set to alarm at twice background (≈ 100 counts per minute above background in low background areas).

- D. Actions if contamination is detected
 - 1. If unit alarms, follow site procedure

Emphasize: DO NOT SPREAD CONTAMINA-TION

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 2. Typical Actions
 - a. Notify Health Physics
 - b. Health Physics actions
 - Additional surveys with other instruments to pinpoint contamination
 - Wipe surveys to determine if contamination is removable
 - Whole body counts to identify internallydeposited radionuclides
- 3. Verification of contamination will require decontamination
- E. Personnel Decontamination Techniques
 - Decontamination of widespread or general contamination
 - a. Shower with tepid water and mild soap
 - Wash to avoid spreading contamination to clean areas
 - Keep contamination out of eyes, nose and mouth
 - Flush with copious water, but minimize total time

There will be some variation from site to site

These are basic actions, level of contamination will determine specific response

TP-7.5

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

· Dry thoroughly

Drying should be accomplished by patting the skin, avoid rubbing. Explain why surface must be dry (minimize attenuation)

- Survey
- Repeat if contamination is still present

Showering maybe used 2 to 3 times if decreases are indicated

 Scrubbing with a <u>soft</u> bristle brush may be used If any scrubbing device is used DO NOT break or abrade the protective skin barrier through excessive scrubbing

- 2. Decontamination of Localized Contamination
 - a. Contamination of eyes, mouth or open wound

TP-7.6

- Flush area freely with water or normal saline
- · Contact physician immediately

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

b. Nasal Contamination

• Blow nose gently several times

Avoid inhaling through nose

 Wet cotton swabs can be used to decontaminate and/or collect samples Swabs should be collected by the individual or a physician only

 Other techniques for decontamination should be administered by physician This may include nasal irrigation

c. Hair decontamination

- Wash hair and dry
- Survey and repeat if necessary

Several washings may be necessary. Process is continued until contamination is removed or no removal is accomplished by washing.

 Medical personnel may be required to trim hair and begin decontamination of the skin if necessary

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

d. Skin decontamination

- Begin with mild soap and tepid water washing. Scrubbing should be performed carefully to not abrade the skin
- Try a mild paste such as a mixture of 50% detergent (Tide, for example) and 50% cornmeal. Commercial decontamination foams or regular shaving foam may be useful

- A chemical agent such as potassium permanganate is usually the next step. Applied to the skin, it removes a small portion of the epidermis and should never be applied to the skin for greater than two minutes. After treatment, the permanganate is decolorized with a solution of sodium bisulfite and the area rinsed with water.
- Decontamination may be accomplished by sweating. Wrapping the affected area in plastic or rubber enhances sweating. Cotton or other absorbent should be used inside the plastic to collect the contamination.

The following list is a generalized sequence, surveys should be performed after each attempt and prior to initiating additional techniques. TP-7.7

The previous techniques should be attempted 3 or 4 times before proceeding.

Chemical decontamination should be conducted under medical supervision

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- Decontamination by waiting for the radioactivity to decay away is used when the radioactive half-life is sufficiently short to permit decontamination in about 30 minutes, and
- Swabs, wipes, adsorbents and decontamination residues should be analyzed for radioactivity identification.
- F. Decontamination of clothing
 - 1. Minimize chance of contamination
 - a. Avoid polyester (synthetic) clothing

Particulates are electrostatically attracted to the clothes

- b. Avoid soft, spongy-soled shoes
- 2. Decontamination Techniques
 - a. Radioactive decay
 - b. Using tape to remove contamination
 - c. Scrubbing with soap and water
 - d. Physically removing contamination sections by cutting

Same process as lint removal

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

G. Work Materials

- 6-4

- 1. Follow site guidance for control of materials
 - a. Bagging while in contaminated areas
 - b. Proper survey requirements and techniques for removal
- 2. Decontamination Techniques
 - a. Follow same general rules for clothing
 - b. Control and reuse in contaminated areas to minimize handling and generating wastes
 - c. Expensive or vital materials may undergo chemical, ultrasonic or abrasion decontamination

Consider cost versus disposal for inexpensive items

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

VIII. USE OF PROTECTIVE CLOTHING

A. Introduction

- 1. Purpose
 - a. Provide instruction, demonstration and practice exercise of the proper techniques for donning and removing protective clothing, including proper actions while inside a radiologically controlled area (RCA) and the follow-up actions after removal of the protective clothing
- 2. Chapter 8 Objectives

TP-8.1

- B. Purpose of Protective Clothing
 - 1. Prevent personnel external contamination
 - 2. Reduce possibility of personnel internal contamination
 - 3. Reduce external exposure (beta radiation)
 - 4. Prevent the spread of contamination

Does not protect/shield from external gamma radiation

- C. Donning Protective Clothing
 - 1. Full set consists of:
 - a. Coveralls
 - b. Shoe covers (flimsies)
 - c. Rubber shoecovers

Assumption: licensee will have specific requirements for a full set of PC's

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- d. Inner Cotton gloves (liners)
- e. Outer rubber gloves
- f. "Surgeon" or skull cap
- g. Cloth hood
- h. Industrial safety equipment (such as safety glasses, and ear plugs, etc.)

Provides the least (if any) amount of protection from contamination, generally provided for comfort

- 2. Donning of protective clothing may vary from one facility to another such as:
 - a. Types of protective clothing
 - b. Protective clothing requirements
 - c. Levels of contamination
- 3. Protective Clothing requirements are set by the Health Physics Supervisor or Manager/Department
 - a. Rules/Regulations must be learned prior to entering area(s) requiring the use of protective clothing
 - b. Each licensee has their own requirements for work in a contaminated area
 - c. Cuts/abrasions may prohibit entry into the RCA-Check with HP prior to entry

"Requirements for work in a Contaminated Area"

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- D. Prior to Donning clothing
 - 1. Review RWP requirement
 - a. Protective clothing
 - b. Job description
 - c. Dosimetry requirements
 - d. Expected dose rates, etc.
 - 2. Select clothing large enough to be removed easily, but not cumbersome
 - 3. Check for holes, tears
 - 4. Check for pinhole leaks in rubber/plastic items
 - 5. Remove outer clothing if necessary or required
 - 6. Remove jewelry and other personal items
 - 7. Place dosimetry in proper location and bag if required
 - 8. Prepare tape pieces for seams

TP-8.2

If clothing is torn while in contaminated area, HP should be notified at area exit

Do not blow open with the mouth. Force air into the item.

Modesty clothing should be worn and may be provided by licensee

TP-8.3

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

 E. Donning Clothing INSTRUCTOR NOTE: Instructor demonstrates dressout procedure while explaining the following sequence				
1.	Seg	quence of donning		
	a.			
	b.			
c. Rubber overshoes				
	d.	Tape ankles	TP-8.4	
e. Safety glasses				
	f.	Cap	TP-8.5	
g. Hood				
h. Dosimetry (normally bagged in thin plastic)				
	i.	Tape coveralls	TP8.6	
	j.	Cotton inner gloves		
	k.	Rubber gloves		
	1.	Tape wrists	TP-8.7	
	m.	Conduct final check	TP-8.8	
2.	Outer rubber gloves and taping performed last due to inconvenience			

Enlist assistance when possible

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

TP-8.13

F.	Re	Removing Clothing			
	1.	Specified by licensee	TP-8.9		
	2.	Normally begin with items most likely to be contaminated			
		a. Overshoes			
		b. Rubber gloves			
		c. Hood			
	3.	Follow licensee procedures at step-off-pad	TP-8.10 Note step-off-		
	4.	Step-off-pad	pads too close together		
		a. Maintain contamination control	TP-8.11 Proper		
		 Do not step on them until contaminated/protective clothing has been removed 	placement at step-off-pad		
	5.	Remove tape and protective clothing slowly			
	6.	Place items in appropriate container at the Step-Off-Pad	TP-8.12		
	7.	Health Physics should be contacted prior to removing tools/materials from a contaminated area			

8-5

8. Remove dosimeters and handle per licensee

9. Do not touch potentially contaminated material

procedures

with cotton liners

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 10. Any mistakes should be reported to HP prior to leaving area
- 11. Conduct whole body monitoring after removal of all protective clothing
 - a. Equipment used includes personnel monitors, baths or hand-held friskers
 - b. Hand held friskers require approximately 3 minutes
 - Ensure unit is on and working properly
 - Check hands first before touching probe
 - Listen and view response
 - Keep probe ½ inch from body
 - Move probe approximately 2 inches per second
 - Repeat hand check after whole body frisk
 - c. Automated units have instructions posted
- 12. Response to monitor/frisker alarms
 - a. Look for posted instructions
 - b. Call for HP assistance

Contact should be avoided to prevent contamination of the probe

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 13. Complete whole body frisk
 - a. Obtain dosimetry and materials used (if any)
 - Check the reading on the pocket dosimeter
 - Complete the RWP sign out and Dose Card
- G. Practical Exercise

INSTRUCTOR NOTE: Use Practical Exercise Evaluation form in Appendix A of the Lesson Outline to evaluate trainee knowledge and ability in RWP requirements and use of protective clothing.

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

IX. INDUSTRIAL SAFETY

A. Introduction

1. Purpose

Provide a general overview of industrial safety practices at nuclear power stations

2. Chapter 9 Objectives

TP-9.1

- 3. Safety is everything we do to prevent accidents and is required for unescorted as well as escorted access
- 4. Each individual has the responsibility to read, understand, and follow the licensee's safety rules

B. Chemical Hazard

- 1. A wide variety of chemicals may be encountered at a nuclear power plant
- 2. The Occupational Safety and Health Administration (OSHA) requires employers to inform employees of the safety and health hazards associated with the use of hazardous chemicals in the workplace (29 CFR 1910.1200)
- 3. Employers (licensees) are required to maintain Material Safety Data Sheets (MSDS) for all chemical hazards used in their workplace
- 4. An MSDS lists the safety precautions to be used when working around a specific chemical

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

a.	Carcinogens	TP-9.2

• Substances which cause cancer

5. Types of Chemical Hazards

	•	Examples of carcinogens are benzidine, inorganic arsenic, and formaldehyde	
b.	Cor	rosives	TP-9.3
	•	Substances which react with sufficient vigor to cause severe injury to living tissue	
	•	Examples of corrosives are sodium hydroxide, nitric and sulfuric acid	TP-9.4
c.	Explosives		
	•	Substances which rapidly react to	

- Substances which rapidly react to produce gases at sufficient temperature and pressure to cause damage
- Examples of explosives are hydrogen and propane TP-9.6

INSTRUCTOR NOTES/KEY AIDS

LESSON OUTLINE

		d.	Gases	TP-9.7	
			 Substances in a physical state that will diffuse to fill a confining spore 		
			 Gases may be hazardous as poisons, flammables, explosives, corrosives or by simply displacing air 		
			• Examples are nitrogen and hydrogen	TP-9.8	
		e.	Poisons	TP-9.9	
			 Substances likely to cause death or serious injury if swallowed, inhaled, or in contact with the skin 		
			• Examples are ammonia and chlorine	TP-9.10	
		f.	Solvents	TP-9.11	
			Substances used to dissolve material and may present several hazards such as toxicity, corrosiveness or flammability	TP-9.12	
			 Examples are cleaning fluids and degreasers 		
C.	Live Steam and Hot Liquids TP-9.13				
	 Live (hot and under pressure) steam and hot liquids can cause severe injury from burns, cutting, and by causing flying fragments 				
	2. Burns from hot components are one of the most frequent causes of injury at a nuclear plant				

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

D. Heat Stress

TP-9.14

- 1. High heat and humidity are principal components which may result in heat stress to personnel
- 2. Common Heat Illness and Symptoms

TP-9.15

- a. Heat cramps
 - · Painful spasms of muscles
- b. Heat exhaustion
 - Fatigue, nausea, headaches, clammy and moist skin, and fainting
- c. Heat Stroke

May be fatal

- Hot dry skin, high and rising temperature, mental confusion, possibly unconscious
- 3. Prevention
 - a. Acclimatize yourself, if possible
 - b. Drink plenty of fluids

Consideration must be given to protective clothing selection when heat stress may be a factor

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

TP-9.19

E.	Cry	vogenics	TP-9.16	
	1.	Substances which are maintained at very low temperatures		
	2.	Contact with cryogenics causes severe damage due to spot freezing of the flesh	The injury is similar in many	
	3.	Examples of cryogenics are liquid oxygen, liquid hydrogen and liquid nitrogen	ways to burns caused by high temperatures	
F.	No	ise	TP-9.17	
	1.	Noise levels can be very high in some plant areas		
	2.	Levels above 90 dBA may cause hearing reduction or loss		
	3.	Hearing loss is permanent		
G.	Oxy	gen_Limited Environment	TP-9.18	
	1.	The lowest oxygen concentration in air permitted by OSHA is 19.5%	-	
	2.	Oxygen deficiencies may be due to displacement, high altitude and oxygen consumption		
•	3.	The most common power plant cause is displacement	Such as that when using argon	

4. Prior to entering potentially oxygen limited environments, remote measurements should be

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

		made	
	5.	Oxygen deficiency may not be sensed and is usually fatal	
H.	Ele	ctrical Shock	TP-9.20
	1.	Electrical shocks most commonly occur while working on open wires, switches and breakers	
	2.	Treat all open electrical components as energized	
	Coı	mpressed Gases	TP-9.21
	1.	Hazards arise from cylinder rupture, leaks and mix-ups	
	2.	Safety action includes carefully checking labels and properly securing cylinders	
J.	Fall	ls	TP-9.22
	1.	Most commonly treated injuries result from falls and trips	
	2.	Biggest safety tip is to stay constantly aware of your environment	TP-9.23 TP-9.24
K.	Gei	neral Safety Practices	TP-9.25
	1.	Safety Equipment	

a. Routinely/required at sites

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- b. Types of equipment
 - Hard hats

Eye protection

TP-9.26

• Ear protection

TP-9.27

- Sturdy shoes
- 2. Postings
 - a. Identify industrial hazards
 - b. Similar to radiation postings
- 3. Tagging
 - a. Tagging materials and equipment unsafe use is a standard practice at all sites
 - b. A RED tag is normally used to prevent operation or movement of an item
- 4. Permits
 - a. Used to control activities with a high chance at industrial safety problems
 - b. Examples are welding, scaffolding, and continued space entry
- L. NRC and OSHA Memorandum of Understanding
 - 1. Described in USNRC Information Notice 88-100

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

2. Delineates general areas of responsibility between NRC and OSHA to minimize workplace hazards X. PHYSICAL PROTECTION AND EMERGENCIES

A. Purpose

- 1. Provide an overview of the physical protection controls and procedures that will be encountered at a nuclear power station and the general procedures for responding to emergencies, drills, and incidents
- B. Chapter 10 Objectives

TP-10.1

C. Physical Protection ("Security") of Plants and Materials

TP-10.2

- 1. Purpose (10 CFR Part 73)
 - a. Protect against acts of radiological sabotage
 - b. Prevent theft of special nuclear material
 - c. Protect safeguards information against unauthorized use
 - d. Prevent unauthorized access into specific areas

D. Definitions

- 1. "Authorized Individual" is an individual...who has been designated in writing by the licensee to have...unescorted access...
- 2. "Isolation Zone" is an area adjacent to a physical barrier which is clear of all objects which could shield an individual

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 3. "Material Access Area" are controlled areas enclosed by barriers and where special nuclear material is present
- 4. "Physical Barrier" means fences, walls, ceilings and floors constructed of...(specific materials, thicknesses, heights, etc.)
- 5. "Protected Area" is an area encompassed by physical barriers and to which access is controlled
- 6. "Safeguards Information" is data, not otherwise classified, which specifically identifies security measures for physical protection and location of certain equipment vital to plant
- 7. "Vital Area" is any area containing vital equipment
- 8. "Vital Equipment" is any equipment, system, device or material; the failure, destruction, or release of which could endanger the public by exposure to radiation

E. Performance Capabilities

TP-10.3

- 1. Licensee must be able to:
 - a. Prevent unauthorized access
 - b. Permit only authorized activities
 - c. Provide for authorized access
 - d. Additional response capabilities associated with the control/movement of special nuclear material

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

F.	Ge	neral	TP-10.4	
	1.	Ow		
		a.	Areas outside barriers are usually not considered part of protection	
		b.	Access routes and general boundaries are posted	
	2.	Pro	stected Area	TP-10.5
		a.	Surrounded by barrier	Normally a fence
		b.	Vehicles/individuals are identified and	TP-10.6
			searched	TP-10.7
		c.	No cameras, weapons, explosives, alcohol, drugs	TP-10.8
		d.	ID badge must be displayed	TP-10.9
		e.	Unescorted access granted must stay in escort's vision	TP-10.10
		f.	Can't challenge existing barriers	
	3.	3. Vital Area		
•		a.	Contains vital equipment whose failure, destruction, or loss of service may endanger the public	
		b.	Normally within the Protected Area	
		c.	Enclosed by a wall	

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

d. Card reader is used for access

TP-10.11

- e. Closed circuit video monitored
- f. Similar rules apply to Protected Area
- g. Door should not be pulled on before unlocking
- h. No tailgating

G. Safeguards Information

- Applies to security plan/procedures, physical protection systems, vital safety equipment and guards
- 2. Access to information on an "as need to know" basis
- 3. Must be clearly identified
- 4. Includes physical protection procedures

H. Emergencies and Drills

- 1. Alarms, sirens, announcements vary from site to site
 - a. Some standardization:
 - Tones for emergency classifications
 - Tones for fire, medical or first aid response

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- Bells/Buzzer for local alarm
- Solid tone for a message or test

2. Response

- a. Obey assembly, evacuation or "stand-fast" orders
- b. Radiological Emergency
 - Exit area and report to designated area
 - 4 levels of emergencies
 - NOUE and Alert require no evacuation
 - SAE and General Emergency usually require evacuation
- c. Fire/Medical Alarm
 - Listen for announcement/standby for further instructions
 - Take appropriate action if emergency can be seen
- d. Local Area Alarm
 - Exit area immediately
 - Report to HP or Safety Department
- e. Unless specific duties are assigned remain out of the way

NOUE, Alert, SAE and General Emergency

Example: Continuous Air Monitor (CAM) Alarm

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- 3. Injuries
 - a. Primary concern-medical treatment
 - b. Take necessary steps to avoid complications
 - c. Know how to request assistance
 - d. Obtain HP approval prior to entering a RCA with an open wound or broken skin
- 4. Incidents
 - a. Radioactive Spill Procedure (SWIMS)

TP-10.12

- Stop the spill
- Warn others
- Isolate the area
- Minimize your exposure
- Secure non-filtered ventilation
- b. Area Radiation/Airborne Alarms

TP-10.13

- Leave area
- Notify HP/Safety

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

- c. Off-Scale, Lost, Damaged Dosimetry
 - Inform others in area
 - Promptly report to HP
 - Greater than \(\) of scale may be treated as "off scale".
- 6. Personnel/Clothing contaminations
 - a. Standby and request HP assistance
- 7. Respiratory Protection Problem
 - a. Immediately leave area
 - b. Remove mask if it becomes difficult to breathe while wearing a respirator
- 8. General Problem/Alarm
 - a. Act with minimal impact to emergency operations

LESSON OUTLINE

INSTRUCTOR NOTES/KEY AIDS

XI. REVIEW

- A. Clarify remaining trainee questions or concerns
- B. Review examination procedure and passing criteria
- C. Administer examination